

**Viscosity1**  
**SAE 0W-20, 5W-20, 5W-30 & 10W-30**  
**Full Synthetic Motor Oil, API SP, ILSAC GF-6A**

**Product Description**

**Viscosity1 SAE 0W-20, 5W-20, 5W-30, and 10W-30** are premium full synthetic motor oils manufactured for use in modern gasoline engines which require ILSAC GF-6A, API SP, API SN Plus, or API SN performance.

These oils are formulated with synthetic base oils and a premium performance additive package which is specially formulated to protect high compression gasoline direct injection engines delivering superior oxidative stability, deposit control, low speed pre-ignition mitigation and timing chain wear protection.

**Typical Properties\***

<b>SAE J300 Viscosity Grade</b>	<b>0W-20</b>	<b>5W-20</b>	<b>5W-30</b>	<b>10W-30</b>
Appearance, Visual	Amber, Transparent, Liquid			
Viscosity @ 40°C, cSt, ASTM D445	44.55	47.75	61.25	68.75
Viscosity @ 100°C, cSt, ASTM D445	8.3	8.3	10.8	10.9
Viscosity Index, ASTM D2270	165	150	170	150
CCS Apparent Viscosity, cP, ASTM D5293	5,400@-35°C	4,800@-30°C	5,200@-30°C	4,900@-25°C
MRV Apparent Viscosity, cP, ASTM D4684	22,000@-40°C	15,000@-35°C	18,000@-35°C	9,000@-30°C
Flash Point, °C, ASTM D92	210	215	215	218
Pour Point, °C, ASTM D97	-47	-44	-42	-40

*\*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.*

**Exceeds Performance Requirements**

API SP with Resource Conserving, API SN Plus, API SN  
 ILSAC GF-6A, GF-5  
 GM dexos1™ Gen 2  
 Chrysler MS6395  
 Ford WSS-M2C947-B1 (0W-20); Ford WSS-M2C945-B1 (5W-20); Ford WSS-M2C946-B1 (5W-30)

**Product Code**

**SAE 0W-20** – VPS002; **SAE 5W-20** – VPS003; **SAE 5W-30** – VPS004; **SAE 10W-30** – VPS005

